

# GTX

ELECTRIC 36 or 48 VOLT  
SOLID PNEUMATIC THREE WHEEL  
3200 / 3600 / 4000 lbs. (1600 / 1800 / 2000 kg)



## STANDARD SPECIFICATIONS

## 16/18/20s

Manufacturer's Designation		GTX 16	GTX 18	GTX 20s
Load Capacity / Rated Load @ 24" LC	lbs(kg)	3200 (1600)	3600 (1800)	4000 (2000)
Height Overhead Guard	in(mm)	81.3 (2066)	81.3 (2066)	81.3 (2066)
Width	in(mm)	43.5 (1105)	43.5 (1105)	45.1 (1146)
Right Angle Stack (Add Load Length and Clearance)	in(mm)	74.6 (1895)	78.9 (2004)	80.7 (2050)
Outside Turning Radius	in(mm)	60.6 (1540)	64.9 (1648)	66.5 (1688)
Travel speed loaded / unloaded	mph (kph)	9.3 (15) / 9.3 (15)	9.3 (15) / 9.3 (15)	9.3 (15) / 9.3 (15)
Power Unit		36/48 Volt	36/48 Volt	36/48 Volt

## STANDARD FEATURES

**Solid pneumatic tires for indoor/outdoor operation • Enclosed motors • Wet disc brakes • Zero turn steer axle • 100% AC Motors • Heavy duty drive motors & axles • Rugged Upright and Carriage • Programmable dash display**



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at [www.clarkmhc.com](http://www.clarkmhc.com).